



BB14P

2-1-2% Accuracy – 4 1/2"-6 Dial Size

Measure two independent pressures on same gauge dial. Top pointer is orange, bottom pointer is black.

STANDARD FEATURES

- Movement:** Bronze Bushed
- Pointer:** Geared Micrometer adjustable, balanced
- Dial:** White enameled aluminum with black graduations and numerals. 270° ARC
- Thread Size:** 1/4 male NPT; 1/2 male NPT*
- Connection Location:** Lower or Rear (back)
- Case:** Suitable for direct or surface mounting. See table below for standard case style. Refer to pages 34-38 for complete description(s), dimensions and optional case styles. A wide choice of polypropylene, aluminum and stainless steel cases is available for direct, surface and flush panel mounting.

*Not available on BB1 series. 1/2 NPT rear connections only available with safety type cases on BB2 and BB4 series

CATALOG NO.	BOURDON TUBE & SOCKET MATERIAL	MAXIMUM PRESSURE (psi)	DIAL SIZE (INCHES)	STANDARD CASE
BB14	Phosphor Bronze Bourdon	1,000	4 1/2	Style "P"
BB16	Forged Brass Socket		6	Style "A"
BB24	Seamless Monel	3,000	4 1/2	Style "4"
BB26	Bourdon and Socket		6	Style "A"
BB44	Stainless Steel, 316		4 1/2	Style "2"
BB46	Bourdon and Socket		6	Style "A"

Note – BB1 series not available with safety cases.

PRESSURE RANGES

CODE NO.	DIAL RANGES	FIGURE INTERVALS	SMALLEST GRADUATION
PD	0-30 psi	5 psi	.5 psi
PE	0-60 psi	10 psi	1 psi
PF	0-100 psi	10 psi	1 psi
PG	0-160 psi	20 psi	2 psi
PH	0-200 psi	20 psi	2 psi
PJ	0-300 psi	50 psi	5 psi
PK	0-400 psi	50 psi	5 psi
PM	0-600 psi	100 psi	10 psi
PO	0-800 psi	100 psi	10 psi
PP	0-1,000 psi	100 psi	10 psi
PR	0-1,500 psi	300 psi	20 psi
PS	0-2,000 psi	200 psi	20 psi
PT	0-3,000 psi	500 psi	50 psi

COMPOUND RANGES

CODE NO.	DIAL RANGES	FIGURE INTERVALS	SMALLEST GRADUATION
CA	30"-0-15 psi	10" & 2 & 15 psi	1" & .5 psi
CB	30"-0-30 psi	10" & 5 psi	1" & 1 psi
CC	30"-0-60 psi	10" & 10 psi	1" & 1 psi
CD	30"-0-100 psi	30" & 10 psi	2" & 1 psi
CE	30"-0-150 psi	30" & 25 psi	5" & 5 psi
CF	30"-0-200 psi	30" & 20 psi	5" & 5 psi
CG	30"-0-300 psi	30" & 50 psi	10" & 5 psi
CI	30"-0-600 psi	30" & 100 psi	10" & 10 psi

NOTES:

1. Regal Duplex Gauges are calibrated in accordance with ASME B40.1 Grade A (± 1% middle third). See page 4 of this catalog for further reference to ASME B40.1.
2. Metric Dials Can be Furnished. See Page 32.
2. BB1 Series not available with safety cases.

HOW TO ORDER

B B 1 4 P C C 4 L W ()

BASIC 4-DIGIT CATALOG NO. FROM TABLE ABOVE _____

CASE STYLE CODE FROM TABLE ABOVE OR OPTIONAL CASE CODE (PAGES 34-38) _____

RANGE CODE FROM RANGE TABLES ABOVE _____

THREAD SIZE: 4 = 1/4 NPT MALE (STANDARD); 2 = 1/2 NPT MALE (SEE NOTATION ABOVE) _____

CONNECTION LOCATION: L = LOWER (BOTTOM); OR R = REAR (BACK) _____

DIAL COLOR: W = WHITE (STANDARD), B = BLACK (OPTIONAL) _____

IF ANY GAUGE OPTIONS ARE DESIRED – SPECIFY OPTION CODE(S) FROM PAGE 33 _____